

DOCUMENT CAMERA

ELMO PX-10

With an unprecedented 288x zoom, the PX-10 captures in vibrant 1080P Full HD resolution and records video at 60fps that can be saved via SD card, USB flash device, or the camera's internal memory. PX-10 comes with a variety of shooting modes including 4:3 and widescreen 16:9, with a capture area of up to A4 portrait and A3 landscape. The PX-10 also features an all-new 5" High-Resolution LCD preview monitor with sleek touch-screen navigation designed for easy camera control, a zoom toggle wheel with autofocus, as well as a variety of output options (HDMI, VGA, and USB). The platform stage is magnetic and comes with a custom white-board surface that can be written on with dry erase markers to show lessons and annotate during demonstrations.



www.visualisers.co.in
www.eassessment.in



ELMO PX-10 SPECIFICATION

MAIN CAMERA

Power Source	DC 5V
Effective Pixels	3840 x 2160 (16:9) 8:3M 3620 x 2640 (4:3) 9:3M
Outside Dimensions	11.7" x 19" x 18.8 (When Setup) 11.7" x 19" x 5.2 (When Folded)
Weight	Approx: 4.5Kg
Lens	F= 2.0
Frame Rate	60fps
Focus Range	Wide: 5 CM ~ ∞/ Tele: 20 CM ~ ∞
Focus Mode	Zoom Sync AF/ One - Push AF
Image Pick-Up Device	12 MegaPixels CMOS
Resolution	1600 TVLines (Center)
Zoom	12x Optical/ 12x Digital/ 2x Sensor
Shooting Area	17" x 12.6" (4:3) Upto A4

VIDEO RECORDING

Recording Media	SD card, SDHC card, SDXC card (class10 or above)
Video Format	H.264 / HEVC(H.265)
File Format	DCF 2.0 compliant (mp4) A thumbnail is created each time a video is recorded. (Extension: thm)
Recording Mode	Normal/ Time-Lapse Recording
Frame Rate	30fps (Fixed)
Audio Recording	Select from the Sound switch menu.
Recording Limit	Maximum video file size: 4GB Maximum video length: 2hours

OUTPUT

HDMI Output	1080p, 720p
RGB Output	1080p, 720p
USB Output	1080p, 720p, QUXGA, UXGA, XGA

IMAGE RECORDING

Recording Media	SD Card, USB Flash Drive, Internal Memory
Image Type	JPEG
File Format	DCF 2.0 compliant A thumbnail is created each time a still picture still picture. (Extension: jpg)

GENERAL SPECIFICATION

LCD Panel	HQ (800x480) 5" Capacitive - Type
Input Terminal	HDMI x2, RGB Dsub15 x1
External Control	RS-232C, USB, Remote Control
Recording/ Play-Back	SD card, USB flash device (only photo), internal memory storage
Audio	INPUT: External microphone (HDMI) OUTPUT: Line out
Image Adjustm-ent	Brightness, White balance, Contrast, Contour Correct, Image Mask
Image Modes	Normal, Emphasis, Color emphasis, Black/White, DLP Projector
Operation Panel	Capture Image, Video Record, Power, AF, Brightness, Freeze, Image Rotation,
illumination	Upper Light (LED)



+91-9999003899 91-9958184884



+91-11-66173727 info@eassessment.in